



ABANICOS LIJADORES CON MANGO

ABANICO LIJADOR CON MANGO F



Ejecución Corindón A



Ref.	Código	Granos suministrables									Ø	Altura	Ø Mango	r.p.m. recomend.	r.p.m. máximas
		40	60	80	120	150	180	240	320	400					
0404600	F 1010/3 A		•	•	•	•	•			•	10	10	3	38.000	75.000
0404601	F 1015/3 A		•	•	•	•	•			•	10	15	3	38.000	75.000
0404602	F 1505/3 A		•	•	•	•	•			•	15	5	3	25.000	50.000
0404603	F 1510/3 A		•	•	•	•	•			•	15	10	3	25.000	50.000
0404604	F 1515/3 A		•	•	•	•	•			•	15	15	3	25.000	50.000
0404605	F 2010/3 A				•	•	•				20	10	3	19.000	28.000
0404606	F 2010/6 A			•	•	•	•				20	10	6	19.000	28.000
0404607	F 2510/6 A			•	•	•	•				25	10	6	15.000	23.000
0404608	F 2515/6 A			•	•	•	•				25	15	6	15.000	23.000
0404609	F 2520/6 A			•	•	•	•				25	20	6	15.000	23.000
0404610	F 2525/6 A			•	•	•	•				25	25	6	15.000	23.000
0404611	F 3005/6 A		•	•	•	•	•		•	•	30	5	6	12.000	18.000
0404612	F 3005/3 A*		•	•	•	•	•		•	•	30	5	3	12.000	18.000
0404613	F 3010/3 A*		•	•	•	•	•		•	•	30	10	3	12.000	18.000
0404614	F 3010/6 A*		•	•	•	•	•		•	•	30	10	6	12.000	18.000
0404615	F 3015/6 A		•	•	•	•	•		•	•	30	15	6	12.000	18.000
0404616	F 3030/6 A		•	•	•	•	•		•	•	30	30	6	12.000	18.000
0404617	F 4010/6 A		•	•	•	•	•		•	•	40	10	6	9.600	18.000
0404618	F 4015/6 A		•	•	•	•	•		•	•	40	15	6	9.600	18.000
0404619	F 4020/6 A		•	•	•	•	•		•	•	40	20	6	9.600	18.000
0404620	F 5010/6 A		•	•	•	•	•		•	•	50	10	6	7.000	12.000
0404621	F 5015/6 A		•	•	•	•	•		•	•	50	15	6	7.000	12.000
0404622	F 5020/6 A		•	•	•	•	•		•	•	50	20	6	7.000	12.000
0404623	F 5030/6 A		•	•	•	•	•		•	•	50	30	6	7.000	12.000
0404624	F 6015/6 A		•	•	•	•	•		•	•	60	15	6	6.300	12.000
0404625	F 6020/6 A		•	•	•	•	•		•	•	60	20	6	6.300	12.000
0404626	F 6030/6 A*	•	•	•	•	•	•		•	•	60	30	6	6.300	12.000
0404627	F 6040/6 A		•	•	•	•	•		•	•	60	40	6	6.300	10.000
0404628	F 6050/6 A	•	•	•	•	•	•		•	•	60	50	6	6.300	10.000
0404629	F 8015/6 A		•	•	•	•	•				80	15	6	4.800	9.000
0404630	F 8020/6 A		•	•	•	•	•				80	20	6	4.800	9.000
0404631	F 8030/6 A*	•	•	•	•	•	•		•	•	80	30	6	4.800	9.000
0404632	F 8040/6 A*		•	•	•	•	•		•	•	80	40	6	4.800	7.000
0404633	F 8050/6 A*	•	•	•	•	•	•		•	•	80	50	6	4.800	7.000

*Abanico según DIN 69183

ABANICO LIJADOR CON MANGO SIC




Ejecución Carburo de Silicio SIC

Ref.	Código	Granos suministrables				Ø	Altura	Ø Mango	r.p.m. recomend.	r.p.m. máximas
		60	80	120	150					
0404700	F 3010/6 C*	•	•	•	•	30	10	6	12.000	18.000
0404701	F 6030/6 C*	•	•	•	•	60	30	6	6.300	12.000
0404702	F 8030/6 C*	•	•	•	•	80	30	6	4.800	9.000

*Abanico según DIN 69183

ABANICO LIJADOR CON MANGO INOX



Ejecución Corindón A INOX

Ref.	Código	Granos suministrables		Ø	Altura	Ø Mango	r.p.m. recomend.	r.p.m. máximas
		60 INOX	80 INOX					
0404800	F 3020/6 A	•	•	30	20	6	12.000	25.400
0404801	F 4020/6 A	•	•	40	20	6	9.600	19.100
0404802	F 5020/6 A	•	•	50	20	6	7.000	15.200
0404803	F 6030/6 A	•	•	60	30	6	6.300	12.700
0404804	F 8050/6 A	•	•	80	50	6	4.800	9.500

4

lijadores

abanicos

abrasivos